PROFESSIONAL OEM/ODM FACTORY

NERNST

Commercial Cake Display Showcase 1200mm SCLG4-410FK3

Refrigerated Bakery Display Cabinet (+2~+8°C / Secop Compressor)

CRAFTSMANSHIP HIGHLIGHTS / 核心卖点

- **High-Efficiency Secop Compressor:** Powered by a genuine Secop compressor for fast pull-down speed, steady temperature control, low vibration, and quiet commercial operation.
- **Ventilated Air-Cooling System:** Circulating air ducts prevent hot spots and eliminate manual defrosting. The consistent +2℃~+8℃ environment keeps pastries, mousses, and cakes fresh and structurally stable without drying them out.
- **Luxury Base & Superior Visibility:** Choice of black/white marble or brushed stainless steel finish. Fitted with high-clarity heated anti-condensation double-pane glass and integrated LED lighting under each shelf to maximize product appeal.



740W	+2~+8°C	220V/50Hz	1 Year
POWER RATING	TEMP RANGE	VOLTAGE	WARRANTY

APPLICATION SCENARIOS / 场景展示

Pastry Boutiques

1. High-End Bakery

Multi-tier glass shelving with crystal-clear anti-fog visibility provides optimal preservation and luxury presentation for fine cakes, desserts, and artisanal pastries.

Shops Scenario

2. Modern Cafes, Juice Bars

Spacious interior depth perfectly accommodates bottled cold brews, dairy milks, and fresh grab-and-go salads with easy customer access.

Hotel Scenario

3. Supermarkets & Hotel

Stainless steel back panel amplifies interior LED illumination, creating an eye-catching merchandising display for dairy, fresh juices, and deli selections.

PRODUCT SPECIFICATIONS / 产品参数

Name / Category	Custom Commercial Refrigerated Cake Display Showcase
Dimensions (W*D*H)	1200 × 700 × 1200 mm
Material & Finish	Premium Stainless Steel / Natural Marble Base
Cooling System	Ventilated / Forced Air Cooling (Frost-free) | Refrigerant: R134a
Compressor & Controller	Heavy-duty Secop compressor | Digital Display
Glass Door Specification	Electric Heated Anti-Condensation Tempered Glass Door (Defogging Function)
Display Levels	3 Display Levels (Bottom base deck + 2 tempered glass shelves)
Voltage / Frequency	220 – 240V 50Hz / 110V 60Hz (Customizable plugs available)