PROFESSIONAL OEM/ODM FACTORY

NERNST

Commercial Luxury Stainless Steel Multi-Deck Showcase

Heavy-Duty SS304 Construction | Ventilated Air Cooling | Electric Heated Anti-Fog Glass

CRAFTSMANSHIP HIGHLIGHTS / 核心卖点

- **Dynamic Air Cooling & Frost-Free:** 3D circulating air cooling eliminates temperature dead corners (+2°C~+8°C), preventing frost build-up and preserving food moisture.
- **Heated Anti-Fog Glass Door:** Built-in electrical heating elements eliminate mist and condensation even in humid conditions, ensuring crystal-clear product view.
- **SS Interior & High-Density Foam:** Stainless steel backdrop reflects LED lighting for a luxurious depth effect, backed by thick polyurethane insulation to save energy.
- **Full OEM/ODM Customization:** Customizable cabinet dimensions (1.2m – 2.0m+), shelf layers, plug configurations, and personalized branding decals.



1600W	+2~+8°C	220V/50Hz	1 Year
POWER RATING	TEMP RANGE	VOLTAGE	WARRANTY

APPLICATION SCENARIOS / 场景展示

Pastry Boutiques

1. High-End Bakery

Multi-tier glass shelving with crystal-clear anti-fog visibility provides optimal preservation and luxury presentation for fine cakes, desserts, and artisanal pastries.

Shops Scenario

2. Modern Cafes, Juice Bars

Spacious 500mm interior depth perfectly accommodates bottled cold brews, dairy milks, and fresh grab-and-go salads with easy customer access.

Hotel Scenario

3. Supermarkets & Hotel

Stainless steel back panel amplifies interior LED illumination, creating an eye-catching merchandising display for dairy, fresh juices, and deli selections.

PRODUCT SPECIFICATIONS / 产品参数

Model / Category	Commercial Multi-Deck Upright Display Chiller (SCLG4-1500FH Series)
Dimensions (W*D*H)	1800 × 700 × 2000 mm (Interior Depth: 500mm | Shelf Depth: 300mm)
Material & Finish	Heavy-Duty SS304 Stainless Steel with Sleek Black Enclosure Frame
Cooling System	Ventilated Dynamic Air Cooling (Frost-Free) | Refrigerant: R404a (R290 optional)
Compressor & Controller	Embraco Commercial Compressor | ECS-2011NEO Microcomputer Digital Display
Glass Door Specification	Electric Heated Anti-Condensation Tempered Glass Door (Defogging Function)
Internal Back Panel	High-Density Cyclopentane Insulation Foam Board + Stainless Steel Liner
Voltage / Frequency	220V / 50Hz (Customizable for 110V/60Hz, 220V/60Hz export standards)